

# 20ES & 20DC

## SHOT BLASTER & DUST COLLECTOR



SPE 20ES  
SHOT BLASTER



SPE 20DC  
DUST COLLECTOR

TECHNICAL SPECS	SPE 20ES	20DC	DESIGN FEATURES
Voltage	380-415V	230V / 460V	<ul style="list-style-type: none"> <li>• Manganese steel construction</li> <li>• Blasting width can be adjusted for line removal and weld inspection</li> <li>• Self-propelled and variable speed drive</li> <li>• Grill fitted into lower separator hopper unit assembly to eliminate foreign objects being allowed into the blastwheel causing damage</li> <li>• Capable of using up to S550 abrasive</li> <li>• Fully machined blastwheel support bearing assembly (eliminates bearing problems and automatically self-aligns blastwheel components)</li> <li>• Can be dismantled to pass through a 24" (600mm) access hole in storage tanks</li> <li>• Removes rubber deposits</li> <li>• Removal of old coatings</li> <li>• Steel preparation to SA3 standard</li> <li>• Provides non-slip surfaces</li> </ul>
Phase	3-Phase		
Blast Motor Output	30hp (22.5kW)	-	
Cycles	60Hz		
Cleaning Width	20.5" (520mm)	-	
Length	59.5" (1511mm)	68.1" (1730mm)	
Width	23.5" (597mm)	31.5" (800mm)	
Height	57" (1448mm)	63" (1600mm)	
Weight	1459lbs (662kg)	770lbs (350kg)	
CFMS	-	1300/1560 ft3/min	

