

16ES & 16DC

SHOT BLASTER & DUST COLLECTOR



**SPE 16ES
SHOT BLASTER**



**SPE 16DC
DUST COLLECTOR**

TECHNICAL SPECS	SPE 16ES	16DC	DESIGN FEATURES
Voltage	380-415V	230V / 460V	<ul style="list-style-type: none"> • Blast unit constructed of manganese steel • Dust collector fitted with integral compressor and reverse air jet pulsation system to allow continuous working • Blasting width can be reduced for line removal and weld inspection • Self propelled variable speed drive allows complete operator control • Grill fitted into lower separator hopper unit assembly to eliminate foreign objects being allowed into the blastwheel causing damage • Capable of using up to S550 abrasive • Fully machined blastwheel support bearing assembly (eliminates bearing problems, automatically self-aligns blastwheel components) • Blastwheel can be rotated in both directions (Optional extra) • Can be dismantled to pass through a 24" (600mm) access hole in storage tanks
Phase	3-Phase		
Blast Motor Output	15hp (11kW) 20hp (15kW)	-	
Cycles	60Hz		
Cleaning Width	16" (406mm)	-	
Length	49" (1250mm)	68" (1730mm)	
Width	20" (510mm)	40.5" (1030mm)	
Height	49" (1250mm)	63" (1600mm)	
Weight	882lbs (400kg)	882lbs (400kg)	
CFMS	-	1300/1560 ft ³ /min	

